

LIQUID CRYSTAL DISPLAY DEVICE AND
METHOD FOR DRIVING A LIQUID CRYSTAL DISPLAY

[0001] This application is based on Japanese patent application Nos. 2000-158570 and 2001-136725, the contents of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to a liquid crystal display device and a method for driving a liquid crystal display, and more particularly to a liquid crystal display device which applies AC pulses to a liquid crystal layer through a plurality of scan electrodes and a plurality of data electrodes which face and cross each other and a method for driving a liquid crystal display.

2. Description of Related Art

[0003] In recent years, various kinds of reflective type liquid crystal displays which use liquid crystal which exhibits a cholesteric phase at room temperature (mainly, chiral nematic liquid crystal) have been studied and developed into media for reproducing digital information into visual information because such liquid crystal displays have advantages of consuming little electric power and of being fabricated at low cost. However, it is well known that such liquid crystal displays with a memory effect have a demerit that the driving speed is low.

[0004] In order to solve this problem, US Patent No. 5,748,277

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] These and other objects and features of the present invention will be apparent from the following description with reference to the accompanying drawings, in which:

Fig. 1 is a sectional view of a liquid crystal display which a driving method according to the present invention is adaptable for;

Fig. 2 is a block diagram which shows a driving circuit of the liquid crystal display;

Fig. 3 is a chart which shows a fundamental driving voltage waveform in the method according to the present invention;

Fig. 4 is a chart which shows a first example of the driving method according to the present invention;

Fig. 5 is a chart which shows a second example of the driving method according to the present invention; and

Fig. 6 is a chart which shows a fundamental driving voltage waveform in a conventional driving method.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0022] Embodiments of a liquid crystal display device and a liquid crystal display driving method according to the present invention are described with reference to the accompanying drawings.

Liquid Crystal Display: See Fig. 1

[0023] First, a liquid crystal display which a driving method according to the present invention is adaptable for is described. The liquid crystal

plurality of strip-like electrodes which are arranged in parallel at fine intervals. The extending direction of the strip-like electrodes 113 and the extending direction of the strip-like electrodes 114 are perpendicular to each other, and the electrodes 113 and the electrodes 114 face each other. Electric power is applied between these upper electrodes and lower electrodes serially, that is, voltages are applied to the liquid crystal 116 serially in a matrix, so that the liquid crystal 116 makes a display. This is referred to as matrix driving. The intersections between the electrodes 113 and 114 function as pixels. By carrying out this matrix driving toward the display layers 111R, 111G and 111B serially or simultaneously, a full-color image is displayed on the liquid crystal display 100.

[0028] A liquid crystal display which has liquid crystal which exhibits a cholesteric phase between two substrates makes a display by switching the liquid crystal between a planar state and a focal-conic state. When the liquid crystal is in the planar state, the liquid crystal selectively reflects light of a wavelength $\lambda = Pn$ (P: helical pitch of the cholesteric liquid crystal, n: average refractive index). When the liquid crystal display is in the focal-conic state, if the wavelength of light selectively reflected by the liquid crystal is in the infrared spectrum, the liquid crystal scatters light, and if the wavelength of light selectively reflected by the liquid crystal is shorter than the infrared spectrum, the liquid crystal transmits visible light. Accordingly, if the wavelength of light selectively reflected by the liquid crystal is set within the visible spectrum and if a light absorbing layer is provided in the side opposite the observing side of the display, the liquid crystal display makes displays as

intermediate colors are possible, and thus, the liquid crystal display 21 can be used as a full-color display.

[0030] The liquid crystal 116 preferably exhibits a cholesteric phase at room temperature. Especially chiral nematic liquid crystal which is produced by adding a chiral agent to nematic liquid crystal is suited.

[0031] A chiral agent is an additive which, when it is added to nematic liquid crystal, twists molecules of the nematic liquid crystal. When a chiral agent is added to nematic liquid crystal, the liquid crystal molecules form a helical structure with uniform twist intervals, and thus, the liquid crystal exhibits a cholesteric phase.

[0032] However, the liquid crystal display with a memory effect is not necessarily of this structure. The resin nodules may be of a wall type or may be omitted. It is possible to structure the liquid crystal display layer to be a polymer-dispersed type composite layer in which liquid crystal is dispersed in a conventional three-dimensional polymer net or in which a three-dimensional polymer net is formed in liquid crystal.

Driving Circuit; See Fig. 2

[0033] As Fig. 2 shows, the pixels of the liquid crystal display 100 are structured into a matrix which is composed of a plurality of scan electrodes R1, R2, ... Rm and a plurality of data electrodes C1, C2, ... Cn (n, m: natural numbers). The scan electrodes R1, R2 ... Rm are connected to output terminals of a scan electrode driving IC 131, and the data electrodes C1, C2, ... Cn are connected to output terminals of a data electrode driving IC 132.

[0034] The scan electrode driving IC 131 outputs a selective signal to a specified one of the scan electrodes R1, R2, ... Rm while outputting a

specified scan electrodes including the part shall be selected. In this way, writing is carried out on only necessary part of the liquid crystal display, which requires a shorter time.

[0038] Writing can be carried out in the above-described way. If an image is displayed on the liquid crystal display, preferably, all the pixels are reset to the same state before writing a new image so that the newly written image will not be influenced by the previously displayed image. The reset of all the pixels may be carried out simultaneously or may be carried out serially by scan electrode.

[0039] When writing on part of the liquid crystal display, the scanning lines in the part to be subjected to writing may be reset serially by scan electrode or may be reset at one time.

Driving Method; See Fig. 3

[0040] First, the principle of a method for driving the liquid crystal display 100 is described. Fig. 3 shows a fundamental voltage waveform applied to liquid crystal in the driving method according to the present invention. The waveform using AC pulses shown in Fig. 3 is only an example, and the driving method according to the present invention does not necessarily use this waveform.

[0041] This driving method generally comprises a reset step, a selection step, an evolution step and a display step. In the reset step, the liquid crystal is reset to a homeotropic state. In the selection step, a voltage to select the final state of the liquid crystal is applied. In the evolution step, the liquid crystal is caused to evolve to the selected final state.

[0042] As Fig. 3 shows, typically, the reset step is divided into a

plurality of alternating cycles, each of which is composed of a positive period and a negative period. In each of the alternating cycles during the reset step, a reset pulse of a voltage $\pm V_r$ is applied to the liquid crystal. Such pulses for one or more cycles are referred to as a reset waveform.

[0043] Likewise, the evolution step is divided into a plurality of alternating cycles. In each of the cycles during the evolution step, an evolution pulse of a voltage $\pm V_e$ is applied to the liquid crystal. Such pulses for one or more cycles are referred to an evolution waveform.

[0044] In the reset step and in the evolution step, a half of each alternating cycle is a polarity maintaining period.

[0045] In the display step, crosstalk pulses which are caused by signals to perform writing on pixels on the other scanning lines are applied. Accordingly, the display step will be also referred to as a crosstalk step in the following paragraphs. The voltage of the crosstalk pulses is smaller than the threshold value to change the state of the liquid crystal. When writing of an image is completed, that is, when all the pixels have gone through the evolution step, the driving ICs 131 and 132 may be stopped so that the voltage applied to the liquid crystal will be 0V.

[0046] In the selection step, a selection pulse is applied. The selection pulse is modulated in accordance with image data, that is, depending on whether the pixel is selected to finally come to a planar state, a focal-conic state or an intermediate state between the planar state and the focal-conic state. Further, it is possible to provide break times (pre-selection step and post-selection step) before and after the time of applying the selection step.

[0047] Next, the state of the liquid crystal is described. First, in the reset step, the reset waveform is applied to the liquid crystal, and thereby, the liquid crystal is reset to a homeotropic state. The form of the selection pulse to be applied to the liquid crystal in the succeeding selection step depends on whether the liquid crystal is desired to finally come to a planar state or to a focal-conic state.

[0048] First, a case of selecting a planar state as the final state of the liquid crystal is described. In this case, in the selection step, an AC selection pulse of a voltage $\pm V_s$ is applied to the liquid crystal, and thereby, the liquid crystal is substantially kept in the homeotropic state. A half of the alternating cycle of the selection pulse is a polarity maintaining period. Thereafter, in the evolution step, the evolution waveform is applied to the liquid crystal. By the application of the evolution waveform, the liquid crystal is kept in the homeotropic state.

[0049] Further, if the pre-selection step and/or the post-selection step are provided, the liquid crystal comes to a slightly twisted state in these steps; however, the final state of the liquid crystal after the evolution step is the same as that in the case of not providing the pre-selection step and the post-selection step. The merit of providing the pre-selection step and the post-selection step is shortening the application time of the selection pulse, and this results in an increase in the driving speed.

[0050] In the display step, 0V or crosstalk pulses which are of a voltage smaller than the threshold value to change the state of the liquid crystal is/are applied to the liquid crystal, and thereby, the liquid crystal comes to a planar state. The liquid crystal in a planar state stays in the state after stoppage of the voltage applied thereto.

[0051] Next, a case of selecting a focal-conic state as the final state of the liquid crystal is described. In this case, in the selection step, a selection pulse of which energy is lower than the energy of the selection pulse for selecting a planar state (for example, a selection pulse of a voltage lower than V_s) is applied. Thereby, the liquid crystal is twisted and comes to a transient state in which the helical pitch is widened approximately double.

[0052] In a case of selecting a focal-conic state, the selection pulse may be 0. In this case, it can be considered that the voltage of the selection pulse is minimized while the polarity maintaining period is kept. Also, it can be considered that the pulse width of the selection pulse is minimized and accordingly, the polarity maintaining period is minimized.

[0053] Thereafter, by application of the evolution waveform, the liquid crystal which has come to a twisted state changes into a focal-conic state. In the display step, as in the case of selecting a planar state, 0V or crosstalk pulses which are of a voltage smaller than the threshold value to change the state of the liquid crystal is/are applied to the liquid crystal. The liquid crystal in a focal-conic state stays in the state after stoppage of the voltage applied thereto.

[0054] Thus, the final state of the liquid crystal depends on the selection pulse applied in the selection step. By changing the voltage and the pulse width of the selection pulse, and more specifically by changing the pulse form applied to each of the data electrode in accordance with image data, intermediate tones can be displayed.

[0055] From the start of the reset step to the end of the evolution step, the liquid crystal is substantially in a transparent state, and accordingly,

the light absorbing layer 121 is seen.

[0056] In the driving method according to the present invention shown by Fig. 3, the polarity maintaining periods of the reset pulses applied to the liquid crystal and the polarity maintaining periods of the evolution pulses applied to the liquid crystal are longer than the polarity maintaining period of the selection pulse applied to the liquid crystal. Also, compared with a conventional driving method shown by Fig. 6, the polarity maintaining periods of the reset pulses in the reset step and those of the evolution pulses in the evolution step of the driving method according to the present invention are longer than those of the conventional method, and on the contrary, the number of polarity inversions in the reset step and that in the evolution step of the driving method according to the present invention are smaller than those of the conventional method. In the driving method shown by Fig. 3, there are three polarity inversions in each of the reset waveform and the evolution waveform. (The reset waveform and the evolution waveform each have two alternating cycles, each of which is composed of a positive period and a negative period.) This contributes to a reduction in consumption of electric power. However, such a decrease in number of polarity inversions of the reset waveform and the evolution waveform shall be in an extent in which an occurrence of residual potential (electrical polarization) of the liquid crystal because of ions in impurities contained in the liquid crystal and degradation of the liquid crystal molecules can be prevented. In each of the reset waveform and the evolution waveform, there shall be at least one polarity inversion and preferably two or more polarity inversions. In such a case, by performing the polarity inversions

in such a way that the number of positive periods and the number of negative periods of the pulses will be equal to each other, an occurrence of residual potential and degradation of liquid crystal molecules can be prevented more effectively.

Driving Example 1; See Fig. 4

[0057] A first example of matrix driving according to the above-described method is described.

[0058] Fig. 4 shows exemplary driving voltage waveforms which act on pixels LCD1, LCD2 and LCD3 which are arranged in a matrix and exemplary pulse waveforms which are applied to scan electrodes (ROW1, ROW2 and ROW3) and to a data electrode (COLUMN) to achieve the driving voltage waveforms. ROW1, ROW2 and ROW3 mean the lines on the scan electrodes, and COLUMN means the line on the data electrode. In this example, a signal which commands transparency, an intermediate tone and total reflection alternately in this order is sent to the data electrode.

[0059] In Fig. 4, for simplification, the reset step and the evolution step are twice as long as the step of applying a selection pulse (selection pulse application step). Actually, however, it is preferred that the reset step and the evolution step are long enough that the liquid crystal can be completely reset and can evolve to the selected state correctly, and usually, the reset step and the evolution step are sufficiently long compared with the selection pulse application step, for example, are tens of times as long as the selection pulse application step.

[0060] In Fig. 4, for simplification of illustration, only one polarity inversion is illustrated both in the reset step and in the evolution step;

03866237.052501

voltage $\pm(V_2+V_4)$ acts on the pixel, and the pixel is selected to finally come to a selective reflection state (planar state). The voltages V_2 and V_4 are appropriate values to select the transparent state and the selective reflection state, and also, the voltage V_4 , which acts on the other pixels as a crosstalk voltage, is a value less than a threshold value to change the state of the liquid crystal.

[0064] In the first example, lines are scanned at uniform time intervals corresponding to the length of the selection pulse application step. In other words, the length of the selection pulse application step is equal to the scanning time. In a case of providing a pre-selection step and a post-selection step, line scanning may be performed at time intervals corresponding to the length of the selection step including the pre-selection step and the post-selection step. In this case, the length of the selection step is equal to the scanning time.

[0065] In Fig. 4, the amplitude of the pulse waveform applied to the scan electrode in the reset step and the amplitude of the pulse waveform applied to the scan electrodes in the evolution step are larger than the maximum amplitude of the pulse waveform applied to the data electrode. In other words, the pulse voltage applied to the data electrode, even at the maximum, is smaller than the pulse voltage applied to the scan electrodes in the reset step and that in the pulse voltage applied to the scan electrodes in the evolution step ($V_1 > V_4$, $V_3 > V_4$) so that crosstalk will not occur. Therefore, the pulse waveform applied to the scan electrode substantially determines the number of polarity inversions and the length of the polarity maintaining periods of the reset waveform and those of the evolution waveform applied to the pixels (liquid crystal). It

is possible to vary the pulse waveforms applied to the scan electrodes independently of each other. By the variation of the pulse waveforms applied to the scan electrodes, the waveforms applied to the pixels can be adjusted line by line in the number of polarity inversions and the length of the polarity maintaining periods.

[0066] In the first example, therefore, compared with the driving method shown by Fig. 6, the polarity maintaining periods of the pulses applied to each of the scan electrodes in the reset step are longer than the polarity maintaining period of the selection pulse acting on the liquid crystal in the selection pulse application step, and the polarity maintaining periods of the pulses applied to each of the scan electrodes in the evolution step are longer than the polarity maintaining period of the selection pulse acting on the liquid crystal. Accordingly, the polarity maintaining periods of the reset waveform and the evolution waveform acting on the liquid crystal become longer than the polarity maintaining period of the selection pulse acting on the liquid crystal, and the number of polarity inversions of the reset waveform and the evolution waveform applied to the liquid crystal can be decreased.

Driving Example 2; See Fig. 5

[0067] A second example of matrix driving according to the driving method is described.

[0068] Waveforms applied to the scan electrodes and the data electrode shown in Fig. 5 are achieved by superimposing a voltage V1 on the respective waveforms shown in Fig. 4. In this case, the waveforms acting on the pixels are of the same waveforms as those shown in Fig. 4.

[0069] In the second example, the polarity maintaining periods of the

pulses applied to each of the scan electrodes in the reset step and the polarity maintaining periods of the pulses applied to each of the scan electrodes in the evolution step are longer than the polarity maintaining period of the selection pulse acting on the pixel in the selection pulse application step. Thereby, the polarity maintaining periods of the reset waveform and the evolution waveform applied to the liquid crystal can be lengthened, and the number of polarity inversions of the reset waveform and the evolution waveform applied to the liquid crystal can be decreased.

Other Embodiments

[0070] The structure, the materials, the producing method of the liquid crystal display are arbitrary. The liquid crystal display is not necessarily of the three-layered structure composed of R, G and B layers and may be of a single layer structure. The voltage values and the times of voltage application illustrated as pulse waveforms are merely examples.

[0071] In the above embodiments, both the polarity maintaining period of the reset pulse and the polarity maintaining period of the evolution pulse are longer than the polarity maintaining period of the selection pulse acting on the pixel in the selection pulse application step; however, it is possible to set only one of the polarity maintaining periods longer than the polarity maintaining period of the selection pulse.

[0072] Although the present invention has been described in connection with the preferred embodiments above, it is to be noted that various changes and modifications are possible to those who are skilled in the art. Such changes and modifications are to be understood as being within the scope of the present invention.